

DLS-265-AB CEILING-SPEAKER WITH 2 DISCRETE SYSTEM-LINES A/B

D
L
S

265

A/B

A / B

S
Y
S
T
E
M

L
I
N
E
S

- **TWO AUTONOMOUS** LOUDSPEAKER PER SYSTEM
- **TWO AUTONOMOUS** 100-VOLT-TRANSFORMER
- ENABLE OPERATION OF SPEAKER VIA **TWO DISCRETE CABLE-LINES**
- IN CASE OF FAILURE OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND-LINE
- **50-HZ-STABLE** TRANSFORMER
- **TOUCH-PROTECTED** 100-V-WAGO-QUICK-CONNECTING-CLAMPS
- OPTIONAL CERAMIC-CONNECTING-CLAMP & THERMO-FUSE AVAILABLE
- **CUSTOM COLOUR & WEATHER-PROOF**-VERSIONS OPTIONAL OBTAINABLE
- OPTIONAL 10W-VERSION & **FIREDOME** AVAILABLE

TECHNICAL DATA:	DLS-265-AB	DLS-265-AB/10W
Loudspeaker:	2 x 15W 165 x 70-mm-Fullrange	2 x 15W 165 x 70-mm-Fullrange
Power-Consumption:	100V-6-3-1.5W	100V-10-5-2.5W
Frequency-Range:	70-20000 Hz	70-20000 Hz
SPL 1W/1m:	92 dB	92 dB
SPL 6W/1m:	100 dB	102 dB
Dimensions:	265 mm x 90 mm	265 mm x 95 mm
Weight:	2 Kg	app. 2,3 Kg
Material:	Metal	Metal
Colour:	RAL 9010 opt. RAL-Classic	RAL 9010 opt. RAL-Classic
Optional:	Firedome FT-265F	Firedome FT-265F

