

CLB-220-DC **DUAL-VOICE-COIL-SYSTEM FOR A/B-SYSTEM-LINES**



C
L
B

220

DUAL
CONE

A / B

- **NO LOSS OF 50% OF THE MEMBRANE-SURFACE IN FAILURE-CASE**
- IN CASE OF BREAKDOWN OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND
- **TWO AUTONOMOUS VOICE-COILS PER SYSTEM**
- LOUDSPEAKER-PROTECTION THROUGH **SPECIAL VOICE-COIL-WINDINGS**
- IN CASE OF **HEAT-OVERLOAD** OF ONE VOICE-COIL, CONTINUOUS FUNCTION OF THE SECOND VOICE-COIL
- TWO AUTONOMOUS **100-VOLT-TRANSFORMER** PER SYSTEM
- **NO PHASE-SHIFT** ON THE MEMBRANE-SURFACE
- **CUSTOM-COLOUR & WEATHER-PROOF-VERSION** OBTAINABLE
- OPTIONAL CERAMIC-CONNECTING-CLAMP & THERMO-FUSE AVAILABLE

S
Y
S
T
E
M

TECHNICAL DATA:	CLB-220-DC	CLB-220-DC/10
Loudspeaker:	6,5" / 2 x 15W with HF-Cone	6,5" / 2 x 15W with HF-Cone
100-V-Taps:	2 x 100V-6-3-1.5W	2 x 100V-10-5-2,5W
Frequency-Range:	70-18 000 Hz	70-18 000 Hz
SPL 1W/1m:	95 dB	95 dB
SPL 6W/1m:	103 dB	105 dB
Dimensions:	220 mm x 95 mm	220 mm x 100 mm
Ceiling Cut-Out:	200 mm	200 mm
Weight:	1,7 Kg	app. 2 Kg
Material:	Metal	Metal
Colour:	white / opt. custom-colour	white / opt. custom-colour
Optional:	Firedome FT-220F	Firedome FT-220F

L
I
N
E
S

