

CLB-220-DC-10W / 30W **DUAL-VOICE-COIL-SYSTEM FOR A/B-SYSTEM-LINES**



C
L
B

220

DUAL
CONE

10W

30W

A / B

S
Y
S
T
E
M

L
I
N
E
S

- **NO LOSS OF 50% OF THE MEMBRANE-SURFACE IN FAILURE-CASE**
- IN CASE OF BREAKDOWN OF ONE LINE, CONTINUOUS FUNCTION OF THE SECOND
- **TWO AUTONOMOUS VOICE-COILS PER SYSTEM**
- LOUDSPEAKER-PROTECTION THROUGH **SPECIAL VOICE-COIL-WINDINGS**
- IN CASE OF **HEAT-OVERLOAD** OF ONE VOICE-COIL, CONTINUOUS FUNCTION OF THE SECOND VOICE-COIL
- TWO AUTONOMOUS **100-VOLT-TRANSFORMER** PER SYSTEM
- **NO PHASE-SHIFT** ON THE MEMBRANE-SURFACE
- **CUSTOM-COLOUR & DAMP-ROOM-VERSION** OBTAINABLE
- OPTIONAL CERAMIC-CONNECTING-CLAMP & THERMO-FUSE AVAILABLE
- OPTIONAL **FIREDOME** AVAILABLE

TECHNICAL DATA:	CLB-220-DC/10W	CLB-220-DC/30W
Loudspeaker:	6,5" / 2 x 30W with HF-Cone	6,5" / 2 x 30W with HF-Cone
100-V-Taps:	2 x 100V-10-5-2,5W	2 x 100V-30-20-10-6-3W
Frequency-Range:	80-18 000 Hz	80-18 000 Hz
SPL 1W/1m:	93 dB	93 dB
SPL MaxW/1m:	103 dB	107 dB
Dimensions without/with FD:	220 mm x 104 mm / 145 mm	220 mm x 104 mm / 145 mm
Ceiling Cut Out :	200 mm	200 mm
Weight:	ca. 1,75 Kg / 2,10 with FD	ca. 1,72 Kg / 2,06 with FD
Material:	Metal	Metal
Colour:	white / opt. custom-colour	white / opt. custom-colour
optional:	Firedome FT-220F	Firedome FT-220F

